



KLEENTEK®

Oil Conditioning Systems

Specifications

Flow Rate:	30 gph (114 lph)
Max. Temp.:	140°F
Operating Temp.:	32°F-120°F
Max. H₂O Content:	500 ppm (options available for >500 ppm)
Electrical Rating:	NEMA 4
Weight:	115 lbs (52.3 kg)
Weight (operating):	140 lbs (63.6 kg)
Power Supply:	115 V/1PH/60Hz 640 Watts (790 Watts with heater kit)
Voltage:	10-12 KVAC
Voltage Cut-Off:	3 KVAC
Cartridge/Set:	1
Collector Part #:	60-0472
Seals:	Viton
Dimensions:	w x l x h 13.75 in x 21.50 in x 21.50 in 34.90 cm x 54.60 cm x 54.6 cm

Replace Collectors:

2,000-4,000 + hours for first set, then 8,000 hours (1 yr.) after initial oil cleanup (less for high load applications).

Change at least once a year for best performance.

Model DOC-N10

Designed for volumes less than 1,050 gallons, Model N10 electrostatically cleans lubricants of contaminants while eliminating the need for mechanical filters. It circulates oil at a very low velocity, removing submicron particles and large contaminants from hydraulic fluids and lubricating oils.



Features

- NEMA 4 rating
- Good for oil reservoirs to 1,050 gallons
- Flow rate of 30 gph